

# HIT-GREEN Lasthebemagnettraverse

## Tragfähigkeitstabellen

HIT-GREEN Traverse 700 kg						
Material-/Wandstärke	mm	≥ 4	≥ 6	≥ 8	≥ 10	≥ 15
Max. Länge der Last	mm	3000	3500	4000	4500	5000
Max. Breite der Last	mm	1500	1500	1500	1500	1500
Max. Traglast	kg	180	260	490	610	700

HIT-GREEN Traverse 1400 kg							
Materialdicke	mm	≥ 4	≥ 6	≥ 8	≥ 10	≥ 15	≥ 20
Max. Länge der Last	mm	3000	3000	4000	4500	5000	5000
Max. Breite der Last	mm	1500	2000	2000	2000	2000	2000
Max. Traglast	kg	180	350	700	800	1130	1400

HIT-GREEN Traverse 4800 kg						
Material-/Wandstärke	mm	≥ 15	≥ 20	≥ 25	≥ 40	≥ 50
Max. Länge der Last	mm	5000	5000	5000	5000	5000
Max. Breite der Last	mm	2000	2000	2500	2500	2500
Max. Traglast	kg	1200	2400	2880	3840	4800

HIT-GREEN Traverse 1000 kg							
Materialdicke	mm	≥ 4	≥ 6	≥ 8	≥ 10	≥ 15	≥ 20
Max. Länge der Last	mm	3000	3000	4000	4500	4500	5000
Max. Breite der Last	mm	1500	1500	1500	1500	1500	1500
Max. Traglast	kg	180	250	300	500	820	1000

HIT-GREEN Traverse 3200 kg						
Material-/Wandstärke	mm	≥ 15	≥ 20	≥ 25	≥ 40	≥ 50
Max. Länge der Last	mm	4000	5000	5000	5000	5000
Max. Breite der Last	mm	2000	2000	2000	2500	2500
Max. Traglast	kg	800	1600	1920	2560	3200